

Material-Datasheet

Product Transparent labels, inkjet, matt

Facematerial	
Material description	Transparent polyester with a matt inkjet-top coating
Hardware	Suitable for all common inkjet printers
Calliper (basic film)	55 µm
Basis weight	55 g/m ²
Adhesive	
Type	Acrylic-dispersion
Peel performance	Permanently adhering with excellent initial adhesion and also on apolare substrates
Coating weight	20 g/m ²
Liner	
Sort	One-sided siliconated, bleached Kraft paper free from wood pulp Amount of silicone = 0,5 – 1,0 g/m ²
Calliper	108 µm
Basis weight	98 g/m ²
Laminate	
Calliper	183 µm
Basis weight	173 g/m ²
Service temperature	–20 °C to +80 °C. For short terms also higher temperatures like e.g. during the application of a laser-printer, do not represent derogation
Min. application temperature	0 °C
Optimal stocking conditions	At ca. 20 °C room temperature and ca. 50 % relative humidity
Packing	
Material	25-sheet-package: GD2 recycled, 400 g/m ²
Disposal	
Upper-/Liner-material	The liner paper is neutral, that is neither a hazardous material nor water polluting. Minor quantities can be added to the wastepaper.
Packaging	Recyclable, please add to wastepaper.