\mathbb{R}

SAFETY DATA SHEET

Q-CONNECT®

1. IDENTIFICATION OF THE SUBSTANCE PREPARATION AND COMPANY UNDERTAKING

1.1 PRODUCT IDENTIFIER

Product name: Lexmark X651de - Toner Cartridge Replacement

Part number: KF17913 - X651HYQCN

1.2 IDENTIFIED USES AND USES ADVISED AGAINST

For use in: Laser Printer of relevant Brand and Model

1.3 **SUPPLIER DETAILS**

Supplier: Interaction-Connect S.A.

296-298 route de Longwy L-1940 Luxembourg Luxembourg

Phone number: +32 9 380 8248

Fax:

E-mail: info@interaction-connect.com

Contact Hours: 09h-17h GMT

1.4 EMERGENCY TELEPHONE NUMBERS

Supplier: +32 9 380 8248 Emergency Hours: 9 AM - 17 PM European Emergency: +351 252 640 230

* This document provides safety-related information about toner contained in print cartridge for use in laser printer

2. HAZARDS IDENTIFICATION

2.1 INFORMATION and CLASSIFICATION

Overview: Product is stable, non-flammable. If used as intended, the product does not present an acute or chronic

health problem. This health hazard assessment is based on information that is available on the

properties of its components.

2.2 **LABEL ELEMENTS**

Applicable Pictograms:

NO PICTOGRAM

Danger Indications: N/A
Risk Phrases: N/A
Safety Phrases: N/A

2.3 OTHER HAZARDS

PBT or vPvB: N/A

Product: Lexmark X651de - Toner Revision date: 07.06.2013 Page: 1/9





3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS number	Weight %	EC Number	Reach (pre/registration) Number	Index number	OSHA PEL	ACGIH TLV	EU Classification
Amorphous Silica (modified)	Trade Secret	1-3%						
Carbon Black	1333-86-4	5-10%		05-2114136296- 49-0000		3,5mg/m ^3 8hours TWA	3,5mg/m ^3 8hours TWA	
Charge control Agent	Trade Secret	0.5-1.5%						
Iron Oxide	1317-61-9	7-13%		05-2114142805- 50-0000				
Polyester Resin	Trade Secret	65-85%						
Polymer WAX	Trade secret	1-5%						
Titaniun Dioxide	13463-67-7	0.1-1%				15 mg/m^3 8hours TWA	10 mg/m^3 8 hours TWA	

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

The Data Shown is in accordance with the latest EC Directives.

This section provides composition information for the toner powder contained in specially designed container inside of the print cartridge.

4. FIRST-AID MEASURES

4.1 FIRST AID MEASURES

4.1.1 FIRST AID INSTRUCTIONS BY RELEVANT ROUTES OF EXPOSURE

Inhalation: Remove to fresh air. If effects occur, consult medical personnel

Eye contact: Flush eyes immediately with plenty of water for at least 15 minutes.

Skin contact: Flush with plenty of water. Use soap.

Ingestion: No adverse effects anticipated by this route of exposure incidental to proper handling.

4.1.2 ADDITIONAL FIRST AID INFORMATION

Additional first aid information: N/A
Immediate Medical Attention Required: N/A

4.2 **SYMPTOMS AND EFFECTS**

Acute Symptoms from Exposure: N/A
Delayed Symptoms from Exposure: N/A

4.3 IMMEDIATE SPECIAL TREATMENT OR EQUIPMENT REQUIRED

Move to fresh air

Product: Lexmark X651de - Toner Revision date: 07.06.2013 Page: 2/9



5. FIRE-FIGHTING MEASURES

5.1 **EXTINGUISHING MEDIA**

Recommended Extinguishing Media: Water, dry chemical, carbon dioxide or foam type axitinguishers.

Extinguishing Media Not to be Used: None.

5.2 **SPECIAL HAZARD**

Unusual Fire/Explosion Hazards: Toner material, like most organic material in powder form, is capable of creating a

dust explosion when in very high quantities (much above a toner crtg), pulverized and

in the presence of an ignition.

Extinguishing Media Not to be Used: None

5.3 ADVICE FOR FIRE FIGHTERS

Avoid inhalation of smoke. Wear protective cloting an wear self-contained breathing apparatus

6. ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

6.1.1 PRECAUTIONS FOR NON-EMERGENCY PERSONNEL

Minimize the release of particulates. Do not use a vacuum cleaner unless motor is rated dust tight.

6.1.2 ADDITIONAL FIRST AID INFORMATION

Avoid breathing dust.

6.1.3 PERSONAL PROTECTION

Wear personal protective equipment as described in Section 8.

6.2 **ENVIRONMENTAL PRECAUTIONS**

Regulatory Information: Keep product out of sewers and watercourses.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANUP

Spill or Leak Cleanup Procedures: After lightly spraying with water to prevent development of dust, spill should be swept up or

wiped up .Then residuals can be removed with soap and cold water. If it is not possible to scrub the floor with water, cover the floor with suitable sheets of paper. These used sheets should be wrapped up in spills and transferred to a suitable container for disposal. Garments may be washed or dry cleaned, after removal of loose toner, always without the presence of

heat to avoid permanent staines.

Product: Lexmark X651de - Toner Revision date: 07.06.2013 Page: 3/9



7. HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Recommendations for Handling: No special precautions when used as intended. Keep containers closed, avoid creating dust.

Keep away from ignition sources.

Advice on General Hygiene: Never eat, drink or smoke in work areas. Practice good personal hygiene after using this

material, especially before eating, drinking, smoking, using the restroom, or applying

cosmetics.

7.2 **CONDITIONS FOR SAFE STORAGE**

Avoid high temperatures, >100°F/32°C

7.3 **SPECIFIC END USES**

Printing Devices

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **CONTROL PARAMETERS**

The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release in order to maintain airborne concentrations of the product below OSHA PELs (See Section 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.2 **EXPOSURE CONTROLS**

Respiratory protection:

IMPROPER USE OF RESPIRATORS IS DANGEROUS. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134 and 1910.137) and, if necessary, wear a NIOSH approved respirator. Select respirator based on its suitability to provide adequate worker protection for given work conditions, levels of airborne contamination, and sufficient levels of oxygen.

Eye/Face Protection:

Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses

Hand/Skin Protection:

For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. WARNING! Air purifying respirators do not protect worker in oxygen deficient atmospheres.

Additional Protection:

N/A

Protective Clothing and Equipment:

Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear splashproof chemical goggles and face shield when working with liquid, unless full face piece respiratory protection is worn.

Safety Stations:

Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment:

Separate contaminated work clothes from street clothes. Launder before reuse. Remove material from your shoes and clean personal protective equipment. Never take home contaminated clothing.

Comments:

Never eat, drink or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the restroom, or applying cosmetics.

Product: Lexmark X651de - Toner Revision date: 07.06.2013 Page: 4/9



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 **DETAIL INFORMATION**

Physical state: Solid. [Toner Cartridge]

Color: Black

Odor: Faint odour (plastic)

Odor threshold: N/A

Melting point:

Flash point:

Solid, not aplicable

Explosion limits:

Not determined

Relative density:

Auto-ignition temperature:

Not applicable

9.2 OTHER INFORMATION

N/A

10. CHEMICAL STABILITY AND REACTIVITY

10.1 Reactivity:

Reactivity Hazards: None

Data on Mixture Substances: None

10.2 **Chemical Stability:** The product is stable. Under normal conditions of storage and use, hazardous

polymerisation will not occur.

10.3 **Hazardous Polymerization:** Stable under conditions of normal use.

10.4 **Conditions to Avoid:** Keep away from heat, flame, sparks and other ignition sources.

10.5 **Incompatible Materials:** Strong oxidising materials

10.6 Hazardous Decomposition: Will not occur.

Product: Lexmark X651de - Toner Revision date: 07.06.2013 Page: 5/9



11. INFORMATION ON TOXICOLOGICAL EFFECT

Mixtures: Toner contains non known toxicological materials.

Acute Toxicity: N/A

Skin Corrosion/Irritation: Tests on toners containing similar materials indicate no evidence of acute dermal toxicity; non-

irritating and non-sensitizing in human patch test.

Serious Eye Damage: Sensitization:Tests on toners containing similar materials indicate non irritating to rabbit eye mucosa.
Tests on toners containing similar materials indicate no evidence of acute inhalation toxicity.

Mutagenicity: Toner is negative (no mutagenic) in the Ames assay

Carcinogenicity: Carbon black is reclassified as a group 2B by IARC, but inhalation tests using a typical toner

showed no association between toner and animal tumours.

Reproductive Toxicity: N/A STOT - Single Exposure: N/A STOT - Multiple Exposure: N/A

Ingestion: Tests on toners containing similar materials indicate no evidence of acute oral toxicity.

Hazard Class Information: N/A Mixture on Market Data: N/A Symptoms: N/A Delayed/Immediate Effects: N/A Test Data on Mixture: N/A Not Meeting Classification: N/A **Routes of Exposure:** N/A **Interactive Effects:** N/A **Absence of Specific Data:** N/A Mixture vs Substance Data: N/A

12. ECOLOGICAL INFORMATION

12.1 **Eco toxicity:** Based on available data, not harmful to aquatic life.

12.2 **Degradability:** Not readily biodegradable.

12.3 **Bioaccumulation Potential:** Bioaccumulation is insignificant.

12.4 **Mobility in Soil:** Partially soluble in water.

12.5 PBT & vPvB Assessment: N/A

12.6 **Other Adverse Effects:** Presents little or no hazard to the environment.

13. DISPOSAL CONSIDERATIONS

Disposal Information:

This product is not regarded as hazardous waste as defined by EU directive 91/689/EEC

Dispose as a solid waste in accordance with local authority regulations.

Empty container retains product residue.

Physical/Chemical Properties that affect Treatment:

Symbol: This product is not classified as dangerous

Risk Phrases: This product is not classified according to the EU regulations.

Waste Treatment Information:

Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations

Personal Protection Required:

Product: Lexmark X651de - Toner Revision date: 07.06.2013 Page: 6/9



14. TRANSPORT INFORMATION

14.1 **UN Number:** None allocated

14.2 UN Shipping Name: N/A

14.3 Hazard Class: N/A

14.4 Packing Group: N/A

14.5 Environmental Hazards: N/A

14.6 **User Precautions:** Handle with care

14.7 Bulk Transport: N/A

GENERAL:

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

15. REGULATORY INFORMATION

EU Regulatory Information:

EPA Regulatory Information: None at this time

CERCLA Reportable Quantity: None

Superfund Information:

Hazard Categories:

Immediate: None

Delayed: None

Fire: None

Pressure: None

Reactivity: None

Section 302 - Extremely Hazardous: Not listed

Section 311 - Hazardous: Not listed

State Regulations:

Other Regulatory Information:

Product: Lexmark X651de - Toner Revision date: 07.06.2013 Page: 7/9

___®

SAFETY DATA SHEET



16. OTHER INFORMATION

This SDS sheet has been made in compliance with EU directive: Reach

General Comments: This information is based on our current knowledge. It should not therefore be construed as

guaranteeing specific properties of the products as described or their suitability for a particular

application

Creation Date of this SDS: 09.04.2013

Data Sources: Supplier info

Classification Methods: Not available

CLP Classification: None

Labeling Phrases: None

Relevant R Phrases: N/A

Relevant S Phrases: N/A

Worker Training: N/A

Product: Lexmark X651de - Toner Cartridge Replacement Revision date: 07.06.2013 Page: 8/9



Key to Abbreviations and Acronyms used in this sheet:

ACGIH = American Conference of Governmental Industrial	N/A = Not Applicable				
Hygienists					
CERCLA = Comprehensive Environmental Response Compensation NFPA = National Fire Protection Association					
and Liability Act					
CLP = Classification, Labeling, and Packaging	NIOSH = National Institute for Occupational Safety and Health				
DSD = Dangerous Substances Directive	OSHA = Occupational Health and Safety Administration				
EC = European Community	PEL = Permissible Exposure Limit				
ECHA = European Chemicals Agency	SCBA = Self Contained Breathing Apparatus				
EPA = Environmental Protection Agency	STOT = Specific Target Organ Toxicity				
EU = Europe or European	TLV = Threshold Limit Value				
GHS = Globally Harmonized System	UK = United Kingdom				
	UN = United Nations				
	•				

DISCLAIMER

All trademarks and models referenced are property of their respective holders and are used for identification purposes only.

These products are not sponsored by, affiliated with, manufactured by or distributed by the named manufacturers.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Product: Lexmark X651de - Toner Revision date: 07.06.2013 Page: 9/9 Cartridge Replacement